Figure X415 **BRASS BODY BALL VALVES**



LOW LEAD COMPLIANT 2 PC FULL PORT* 600 WOG

Features:

- 600 WOG Non-Shock
- 400 PSI Maximum for FM Approved Applications
- 150 WSP
- Full Port*
- NSF 61 Annex G Certified (UL) (Annex G references NSF 372)
- Threaded NPT Ends (ANSI B1.20.1)
- Forged Brass Body & Endcap
- 100% Electronically Tested in Open & Closed Position at 80 PSI
- Meets MSS SP-110 Standards
- FM & CSA Approved (1/2"~2")
- · Blow-out Proof Stem
- Dual O-ring Non-adjustable Packing**
- Accessories (Sold Separately)
 - Lock Lever Kit (1/4"~4")
 - Stem Extension Kit (1/4"~4")
 - Tee Handle Kit (1/4"~1")
 - Oval Handle Kit (1/4"~2")
 - Memory Stop Kit (1/4"~2")
 - Stainless Handle (1/4"~2")
 - * 4" Valve is Standard Port
 - ** 1/4" & 3/8" Utilize one o-ring, one packing ring and adjustable packing nut

NOT FOR USE AT OR BELOW GROUND LEVEL

Low Lead Compliant: Referring to laws defining "Lead Free" as wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$ per the Safe Drinking Water Act (Sec. 1417) amended 1-4-2011 as well as other state regulations.











Locking Handle Kits



Memory Stops

Stainless Steel Handle







1/2" ~ 2"


Gas Approvals

- CSA Clas 3371-08, ANSI Z21, 15/CSA9, 1, 1/2 PSIG, -40°F~149°F
- CSA Class 3371-10, CGA 3.16, 125 PSIG, -40°F~149°F
- CSA Class 3371-12, CR91-002, 2 & 5 PSIG, -40°F~149°F
- CSA Class 3371-88, ANSI Z21.15/CSA9.1, 1/2 PSIG, -40°F~149°F
- CSA Class 3371-90, ASME B16.33/B16.38, 125 PSIG, -40°F~149°F
- CSA Class 3371-92, ASME B16.44, 5 PSIG, -40°F~149°F

Figure Number Matrix

FNW X415 <u>S</u>	<u>ize</u>
	CODE
3/8 = C	
3/4 = F	2-1/2 = L 3 = M
1 = G 1-1/4 = H	4 = P

Kit Codes (Order Separately)



www.fnw.com

Extension Kits





Figure X415 **BRASS BODY BALL VALVES**

LOW LEAD COMPLIANT 2 PC FULL PORT* 600 WOG

Ref.

Sizes 1/4" & 3/8"





Ref. No.	Description	Material	Qty	Remarks
1	Body	Brass CW 510L	1	
2	Ball	Brass CW 510L (TEA Plated)	1	Solid ball 1/4" to 3/4" Hollow ball 1" & larger
3	End Cap	Brass CW 510L	1	
4	Seat	PTFE	2	
6	Stem	Brass CW 510L (TEA Plated)	1	
7	Stem Packing	PTFE	1	1/4" & 3/8" only
7A	Stem O-ring	NBR	1	
7B	Stem O-ring	FKM	1	1/2" & larger only
8	Handle	Steel DD11	1	
9	Handle Sleeve	Vinyl	1	
10	Thrust Washer	PTFE	1	
11	Gland Nut	Steel CL 04	1	1/4" & 3/8" only
11A	Packing Gland	Brass CW 614N (Nickel Plated)	1	1/4" & 3/8" only
13	Handle Nut	Steel CL 04	1	


Standard Materials

Dimensions (inches)

			•	
Size	ØD	E	L	Н
1/4	0.39	3.78	2.03	1.67
3/8	0.39	3.78	2.03	1.67
1/2	0.55	3.78	2.22	1.77
3/4	0.75	4.76	2.46	2.22
1	0.94	4.76	3.01	2.32
1-1/4	1.19	5.94	3.37	2.85
1-1/2	1.50	5.94	3.70	3.09
2	1.95	6.30	4.33	3.70
2-1/2	2.44	8.07	5.16	4.59
3	2.99	8.07	5.94	4.98
4	2.99	8.07	6.50	4.98

Cv & Weights

Size	Cv	Wt. (Lbs)
1/4	6	0.34
3/8	7	0.30
1/2	19	0.40
3/4	34	0.70
1	45	0.97
1-1/4	75	1.63
1-1/2	180	2.17
2	210	3.83
2-1/2	400	6.69
3	650	9.88
4	650	12.51



DOC: FNWX41513 Ver. 4/2014

© 2014 - FNW. All rights reserved.

The FNW logo is a trademark of Ferguson Enterprises, Inc., PL Sourcing, PO Box 2778, Newport News, VA 23609

The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice. Always verify that you have the most recent product specifications or other documentation prior to the installation of these products.

Figure X416 **BRASS BODY BALL VALVES**



LOW LEAD COMPLIANT 2 PC FULL PORT 600 WOG

Features:

- 600 WOG Non-Shock
- 150 WSP
- Full Port
- NSF 61 Annex G Certified (UL) (Annex G references NSF 372)
- Sweat Ends (ANSI B16.18)
- Forged Brass Body & Endcap
- 100% Electronically Tested in Open & Closed Position at 80 PSI
- Meets MSS SP-110 Standards
- Blow-out Proof Stem
- Dual O-ring Non-adjustable Packing
- Accessories (Sold Separately)
 - Lock Lever Kit (1/2"~3")
 - Stem Extension Kit (1/2"~3")
 - Tee Handle Kit (1/2"~1")
 - Oval Handle Kit (1/2"~2")
 - Memory Stop Kit (1/2"~2")
 - Stainless Handle (1/2"~2")

NOT FOR USE AT OR BELOW GROUND LEVEL



Accessories







Stem

Low Lead Compliant: Referring to laws defining "Lead Free" as wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content \leq 0.25% per the Safe Drinking Water Act

(Sec. 1417) amended 1-4-2011 as well as other state

regulations.

COMPLIANT

Stops




Handle

Figure Number Matrix

FNW X416 <u>S</u>	ize
SIZE	CODE
1/2 = D	1-1/2 = J
3/4 = F	2 = K
1 = G	2-1/2 = L
1-1/4 = H	3 = M

Kit Codes (Order Separately)




www.fnw.com

Extension Kits



Figure X416 BRASS BODY BALL VALVES

LOW LEAD COMPLIANT 2 PC FULL PORT 600 WOG




Cv & Weights					
Size	Cv	Wt. (Lbs)			
1/2	19	0.39			
3/4	34	0.63			
1	45	0.88			
1-1/4	75	1.63			
1-1/2	180	2.28			
2	210	4.09			
2-1/2	400	6.89			
3	650	9.76			

Standard Materials

Ref. No.	Description	Material	Qty	Remarks
1	Body	Brass CW 510L	1	
2	Ball	Brass CW 510L (TEA Plated)	1	Solid ball 1/2" & 3/4" Hollow ball 1" & larger
3	End Cap	Brass CW 510L	1	
4	Seat	PTFE	2	
6	Stem	Brass CW 510L (TEA Plated)	1	
7A	Stem O-ring	NBR	1	
7B	Stem O-ring	FKM	1	
8	Handle	Steel DD11	1	
9	Handle Sleeve	Vinyl	1	
10	Thrust Washer	PTFE	1	
13	Handle Nut	Steel CL 04	1	

Dimensions (inches)

Size	ØD	Е	L	L1	Н
1/2	0.55	3.78	2.19	0.50	1.77
3/4	0.75	4.76	2.78	0.75	2.22
1	0.94	4.76	3.37	0.91	2.32
1-1/4	1.19	5.94	3.86	0.97	2.85
1-1/2	1.50	5.94	4.48	1.10	3.09
2	1.95	6.30	5.33	1.34	3.70
2-1/2	2.44	8.07	6.14	1.48	4.59
3	2.99	8.07	7.17	1.67	4.98



DOC: FNWX41613 Ver. 4/2014

© 2014 - FNW. All rights reserved.

The FNW logo is a trademark of Ferguson Enterprises, Inc., PL Sourcing, PO Box 2778, Newport News, VA 23609

The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice. Always verify that you have the most recent product specifications or other documentation prior to the installation of these products.